

# AERIS

WALL LIGHT

Inspired by the ethereal beauty of clouds, Aeris embodies softness and lightness, crafting an ethereal wall light. Each mouth blown glass cloud is paired with an architecturally crafted brass wall canopy.

Available in four distinctive tones, each variation transforms the fixture's presence in a unique way: a soft white glow, the warmth of the morning sun, the subtle shimmer of a silver lining. Every cloud carries its own delicate texture, formed naturally in the glassblowing process, diffusing light into a gentle, ambient glow.


## AVAILABLE FINISHES

FROSTED BLACK GLASS · BLACK GLASS · CLEAR GLASS · WHITE GLASS · BRUSHED BRASS · BRUSHED BLACKENED BRASS · BRUSHED BRONZED BRASS

## TECHNICAL

| | |
|---|---|
| MATERIAL | TREATED BRASS, GLASS |
| FINISH | ALL BRASS COMPONENTRY IS BRUSHED AND TREATED TO ACHIEVE THE AVAILABLE FINISH OPTIONS, THEN SEALED TO PREVENT ACCELERATED AGING. |
| LAMPING | SELV 60V (WITH EXTERNAL DRIVER)<br>3.7W, 2700K<br><br>LUMEN OUTPUT BASED ON FINISH<br>CLEAR - 440LM WHITE - 430LM<br>FROSTED BLACK - 130LM BLACK - 230LM |
| DIMMING | 220-240V REGION<br>PHASE DIMMING RANGE 5 - 100%<br>DALI DIMMING RANGE 1 - 100%<br><br>110-120V REGION<br>PHASE DIMMING RANGE 3 - 100%<br>DALI DIMMING RANGE 0.1 - 100%<br><br>ALL US AND CANADIAN ORDERS COME SUPPLIED WITH 120V COMPONENTRY CERTIFIED FOR USE IN THESE REGIONS.<br><br>FOR OPTIMAL DIMMING PERFORMANCE WE RECOMMEND SOURCING A DIMMER CAPABLE OF SETTING THE DIMMING RANGE OF THE FIXTURE. |
| LED LIFESPAN | 50,000 HRS |

## DIMENSIONS



AEW
Ø 245 D 155
Ø 9.6" D 6.1"

| | |
|---|---|
| IP RATING | IP20 - FOR INDOOR USE ONLY |
| CERTIFICATION | AU/NZ AS/NZS 60598.1, 60598.2.1<br>EU EN 60598.1, 60598.2.1<br>US/CAN UL1598, CSA C22.2#250.0 |
| WALL MOUNT | AEW - Ø 110 / Ø 4.3"<br>DESIGNED TO CONCEAL 4" OCTAGONAL JUNCTION BOXES. |
| DRIVER SIZE | |
| 220 -240V PHASE | L101 X W51 X H29 / L4" X W2" X H1.1" |
| 220-240V DALI | L145 X W30 X H21 / L5.7" X W1.2"/ X H0.9" |
| 110-120V TRIAC | *L75 X W35 X H26.5 / L3" X W1.4" X H1" |
| 110-120V DALI | *L75 X W35 X H26.5 / L3" X W1.4" X H1" |
| | *DRIVER CAN BE HOUSED WITHIN STANDARD 4" OCTAGONAL JUNCTION BOX. |
| SKU CODES | EG. AEW.G-WHT.BR-BRZ<br>AERIS WALL LIGHT IN WHITE GLASS WITH A BRUSHED BRONZED BRASS WALL MOUNT<br><br>AEW.G-XXX.BR-XXX<br><br>GLASS<br>FROSTED BLACK (G-FBL)<br>BLACK (G-BLK)<br>WHITE (G-WHT)<br>CLEAR (G-CLR)<br><br>FRAME<br>BRUSHED BRASS (BR-NAT)<br>BRUSHED BLACKENED BRASS (BR-BLK)<br>BRUSHED BRONZED BRASS (BR-BRZ) |
| PRODUCT WEIGHT | 3KG / 6.6LB |
| PACKAGE WEIGHT | 3.5KG / 7.7LB |
| PACKAGE SIZE | 1 X L 320 W 320 H 300 / L 12.6" W 12.6" H 11.8" |