

SOLACE

PENDANT

Solace is a luminous glass tear that transforms with movement, revealing two distinct identities in light and form. Through the exploration of geometric form the interplay of two perpendicular, intersecting circles serve as the foundation for this intricate composition.

Visually enchanting, Solace emerges from a series of experiments that use innovative engineering and push the boundaries of traditional glassblowing techniques.

AVAILABLE FINISHES

FROSTED BLACK GLASS · FROSTED CLEAR GLASS · WHITE GLASS · BRUSHED BRASS · BLACKENED BRASS · BRONZED BRASS

TECHNICAL

MATERIAL	TREATED BRASS, GLASS
FINISH	ALL BRASS COMPONENTRY IS BRUSHED AND TREATED TO ACHIEVE THE AVAILABLE FINISH OPTIONS, THEN SEALED TO PREVENT ACCELERATED AGING.
LAMPING	SELV 60V (EXTERNAL DRIVER SUPPLIED) 8W, 2700K LUMEN OUTPUT BASED ON FINISH WHITE - 700LM FROSTED CLEAR - 700LM FROSTED BLACK - 500LM
DIMMING	220-240V REGION PHASE DIMMING RANGE 5 - 100% DALI DIMMING RANGE 1 - 100% 110-120V REGION PHASE DIMMING RANGE 3 - 100% DALI DIMMING RANGE 0.1 - 100% ALL US AND CANADIAN ORDERS COME SUPPLIED WITH 120V COMPONENTRY CERTIFIED FOR USE IN THESE REGIONS. FOR OPTIMAL DIMMING PERFORMANCE WE RECOMMEND SOURCING A DIMMER CAPABLE OF SETTING THE DIMMING RANGE OF THE FIXTURE.
LED LIFESPAN	50,000 HRS
IP RATING	IP20 - FOR INDOOR USE ONLY
CERTIFICATION	AU/NZ AS/NZS 60598.1, 60598.2.1 EU EN 60598.1, 60598.2.1 US/CAN ETL/UL CERTIFICATION PENDING
CANOPY	VARIOUS - SEE CANOPY OPTIONS ON FOLLOWING PAGE
DRIVER SIZE	
220 -240V PHASE	L101 X W51 X H29 / L4" X W2" X H1.1"
220-240V DALI	L145 X W30 X H21 / L5.7" X W1.2"/ X H0.9"
110-120V TRIAC	*L75 X W35 X H26.5 / L3" X W1.4" X H1"
110-120V DALI	*L75 X W35 X H26.5 / L3" X W1.4" X H1"
	*DRIVER CAN BE HOUSED WITHIN STANDARD 4" OCTAGONAL JUNCTION BOX.
SKU CODES	EG. SOP.G-FCL.BR-BLK SOLACE PENDANT IN FROSTED CLEAR GLASS WITH A BLACKENED BRASS BODY SOL.G-XXX.BR-XXX GLASS FROSTED BLACK (G-FBL) FROSTED CLEAR (G-FCL) WHITE (G-WHT) BODY BRUSHED BRASS (BR-NAT) BLACKENED BRASS (BR-BLK) BRONZED BRASS (BR-BRZ)
PRODUCT WEIGHT	6KG / 13.2LB
PACKAGE WEIGHT	7KG / 15.5LB
PACKAGE SIZE	L 360 W 360 H 550 / L 26" W 26" H 34"

DIMENSIONS



L 195 W 195 H 690
L 7.7" W 7.7" H 51"
MIN DROP HEIGHT - H 850 / 33.5"

TECHNICAL

MATERIAL	TREATED BRASS
CANOPY FINISH	BRUSHED BRASS (BR-NAT) BLACKENED BRASS (BR-BLK) BRONZED BRASS (BR-BRZ)
SKU CODES	EG. CAN.SL.F14.BR-BLK = SLIM FIXED CANOPY IN BLACKENED BRASS FINISH

BRUSHED BRASS · BLACKENED BRASS · BRONZED BRASS

AVAILABLE CANOPIES

ALL ROSS GARDAM CEILING MOUNTED FIXTURES COME SUPPLIED WITH A CEILING CANOPY UNLESS OTHERWISE SPECIFIED. EACH CANOPY INCLUDES ELECTRICAL CONNECTORS, EARTH WIRE AND CABLE RETENTION TO CONNECT TO MAINS POWER. THE BELOW IMAGES DEPICT THE CEILING CANOPIES AVAILABLE WITH EACH FIXTURE TYPE. IF NO CANOPY IS SELECTED, THE SLIM CANOPY WILL BE SUPPLIED.



SLIM
Ø14MM FIXED CANOPY
CAN.SL.F14.XX-XXX

Ø120 X 7MM / 4.7" X 0.3"

DRIVER HOUSED IN CEILING OR JUNCTION BOX



SLIM
Ø14MM FIXED SWIVEL CANOPY
CAN.SL.F14.SW.XX-XXX

Ø120 X 7MM / 4.7" X 0.3"

DRIVER HOUSED IN CEILING OR JUNCTION BOX



PUCK*
Ø14MM FIXED CANOPY
CAN.PK.F14.XX-XXX

Ø50 X 65MM / 2" X 2.6"

DRIVER HOUSED IN CEILING
*US/CAN ORDERS TO BE INSTALLED WITH SUPPLIED JUNCTION BOX RENDER MOUNTING PLATE



PUCK*
Ø14MM FIXED SWIVEL CANOPY
CAN.PK.F14.SW.XX-XXX

Ø50 X 65MM / 2" X 2.6"

DRIVER HOUSED IN CEILING
*US/CAN ORDERS TO BE INSTALLED WITH SUPPLIED JUNCTION BOX RENDER MOUNTING PLATE



LARGE
Ø14MM FIXED CANOPY
CAN.ST.170.F14.XX-XXX

Ø170 X 40MM / 6.7" X 1.6"

DRIVER HOUSED IN CANOPY



LARGE
Ø14MM FIXED SWIVEL CANOPY
CAN.ST.170.F14.SW.XX-XXX

Ø170 X 40MM / 6.7" X 1.6"

DRIVER HOUSED IN CANOPY

*HANG HEIGHT NEEDS TO BE CONFIRMED PRIOR TO PRODUCTION, TOLERANCE IS +/- 25MM
*POWER ACCESS POINT REQUIRED AT CENTRE OF CEILING CANOPY.