

## New View

design iGuzzini/Arup



### Features



- Installation on three-phase track and on a ceiling-mounted base.
- Made of die-cast aluminium and thermoplastic material.
- Super-pure aluminium optics.
- High visual comfort (when using accessories).
- 90° tilting on horizontal plane; 360° rotation around vertical axis with mechanical aiming lock.

- PCB linear LED with passive dissipation and high luminous efficiency.
- Complete with protection screen.




### Wall-mounted

View is available in wall-mounted version



**Optics and lamps**



Wall Washer



**SF**  
Super Flood



**LED**

14 - 17 - 29W

33 - 43W

**Correct installation**

Please refer to the instructions sheet for the best layout of the fixtures in order to guarantee uniform wall lighting.




**LED**

**Energy saving**

- **LED Single chip**
- Colour stability **Mac Adam <3**
- Life 50000 h **L80 B10**
- Color temperature:  
Neutral white **4000K**  
Warm white **3000K**

lumen lm	LED	QR CBC 51	ENERGY SAVING
<b>1500</b>	17W	2x35W	76%
<b>3000</b>	33W	3x50W	78%

(3000K) LED energy saving compared with conventional lamps




47  
WHITE/BLACK


04  
BLACK

**spotlight**

**new**  
Very Wide Flood versions: available for order  
Wall Washer versions: available for order from first quarter



light source	W	lm	optic	code colour
<b>LED new</b> 4000K - CRI 80	14 W	1500	SF	<b>P128</b> 47-04
3000K - CRI 80	17 W	1500	SF	<b>N983</b> 47-04
3000K - CRI 90	17 W	1300	SF	<b>N984</b> 47-04
4000K - CRI 80 - DALI	14 W	1500	SF	<b>P636</b> 47-04
3000K - CRI 80 - DALI	17 W	1500	SF	<b>P637</b> 47-04
3000K - CRI 90 - DALI	17 W	1300	SF	<b>P638</b> 47-04



light source	W	lm	optic	code colour
<b>LED new</b> 4000K - CRI 80	14 W	1500	WW	<b>P007</b> 47-04
3000K - CRI 80	17 W	1500	WW	<b>P008</b> 47-04
3000K - CRI 90	17 W	1300	WW	<b>P009</b> 47-04
4000K - CRI 80 - DALI	14 W	1500	WW	<b>P645</b> 47-04
3000K - CRI 80 - DALI	17 W	1500	WW	<b>P646</b> 47-04
3000K - CRI 90 - DALI	17 W	1300	WW	<b>P647</b> 47-04




light source	W	lm	optic	code colour
<b>LED new</b> 4000K - CRI 80	29 W	3000	SF	<b>N994</b> 47-04
3000K - CRI 80	33 W	3000	SF	<b>N995</b> 47-04
3000K - CRI 90	33 W	2500	SF	<b>N996</b> 47-04
4000K - CRI 80 - DALI	29 W	3000	SF	<b>P639</b> 47-04
3000K - CRI 80 - DALI	33 W	3000	SF	<b>P640</b> 47-04
3000K - CRI 90 - DALI	33 W	2500	SF	<b>P641</b> 47-04



light source	W	lm	optic	code colour
<b>LED new</b> 4000K - CRI 80	29 W	3000	WW	<b>P019</b> 47-04
3000K - CRI 80	33 W	3000	WW	<b>P021</b> 47-04
3000K - CRI 90	33 W	2500	WW	<b>P022</b> 47-04
4000K - CRI 80 - DALI	29 W	3000	WW	<b>P648</b> 47-04
3000K - CRI 80 - DALI	33 W	3000	WW	<b>P649</b> 47-04
3000K - CRI 90 - DALI	33 W	2500	WW	<b>P650</b> 47-04



light source	W	lm	optic	code colour
<b>LED new</b> 4000K - CRI 80	43 W	4000	SF	<b>P000</b> 47-04
3000K - CRI 80	43 W	3600	SF	<b>P002</b> 47-04
3000K - CRI 90	43 W	3000	SF	<b>P003</b> 47-04
4000K - CRI 80 - DALI	43 W	4000	SF	<b>P642</b> 47-04
3000K - CRI 80 - DALI	43 W	3600	SF	<b>P643</b> 47-04
3000K - CRI 90 - DALI	43 W	3000	SF	<b>P644</b> 47-04



light source	W	lm	optic	code colour
<b>LED new</b> 4000K - CRI 80	43 W	4000	WW	<b>P026</b> 47-04
3000K - CRI 80	43 W	3600	WW	<b>P027</b> 47-04
3000K - CRI 90	43 W	3000	WW	<b>P028</b> 47-04
4000K - CRI 80 - DALI	43 W	4000	WW	<b>P651</b> 47-04
3000K - CRI 80 - DALI	43 W	3600	WW	<b>P652</b> 47-04
3000K - CRI 90 - DALI	43 W	3000	WW	<b>P653</b> 47-04




wall-mounted

new  
Available for order from first quarter

light source	W	lm	optic	code	colour
<b>LED new</b> 4000K - CRI 80					
29W	3000	WW	<b>N988</b>	47	
3000K - CRI 80					
33W	3000	WW	<b>N989</b>	47	
4000K - CRI 80 - DALI					
29W	3000	WW	<b>N990</b>	47	
3000K - CRI 80 - DALI					
33W	3000	WW	<b>N991</b>	47	



light source	W	lm	optic	code	colour
<b>LED new</b> 4000K - CRI 80					
43W	4000	WW	<b>N992</b>	47	
3000K - CRI 80					
43W	3600	WW	<b>N993</b>	47	
4000K - CRI 80 - DALI					
43W	4000	WW	<b>P013</b>	47	
3000K - CRI 80 - DALI					
43W	3600	WW	<b>P014</b>	47	



spotlight accessories



130



170



210

	code	colour	code	colour	code	colour
Antiglare screen	<b>MXV7</b>	04	<b>MXV8</b>	04	<b>MXV8</b>	04
Asymmetrical screen	<b>MXV9</b>	04	<b>MXW0</b>	04	<b>MXW0</b>	04
Ceiling base	<b>MXZ2</b>	01-04	<b>MXZ2</b>	01-04	<b>MXZ2</b>	01-04
Recessed base Hole for installation 108 mm	<b>MXZ3</b>	01-04	<b>MXZ3</b>	01-04	<b>MXZ3</b>	01-04
Cover for adapter IP40	<b>MXZ5</b>	01-04	<b>MXZ5</b>	01-04	<b>MXZ5</b>	01-04